

Share My Screen 4K

USB-C Wireless Display Adapter with Hub WDA-02





Wireless display adapter



Video resolution up to 4K



HDMI video connection



USB-A hub function

Wireless Presenting in 4K

Share My Screen 4K is a game changer, providing plugand-play 4K HDMI output with pristine clarity at 30Hz. Enjoy wireless freedom with a 10-meter display range, ideal for presentations, streaming, and gaming without the hassle of cables.

Effortless pairing ensures quick and secure connections, catering to all levels of technical expertise. It connects smartphones, tablets, and laptops to monitors, TVs, and projectors and is universally compatible with USB-C devices. Extend your range and roam up to 10 metres without losing signal.

The additional USB-A port allows you to connect your mouse, keyboard, or external memory. The WDA-02 is your sleek solution for on-the-go presentations—ideal for professionals and students who need seamless connectivity anywhere, at any time.

www.verbatim.com



Share My Screen 4K

USB-C Wireless Display Adapter with Hub WDA-02

General Information	
Material	ABS
Colour	Black/Grey
Compatible devices	Transmitter: Notebook, Tablet PC, Smartphone Receiver: TV, Monitor, Projector
Transmission distance	Max. 10 meters
Transmitter	
Dimensions	82mm x 80mm x 14.5mm LxWxH
USB connector	USB-C™
USB interface	USB 2.0
USB data transmission	Support USB-C 2.0 480Mbps
USB data transfer	USB-A 2.0 port (for mouse, keyboard, external memory, etc.)
Video	Support DP Alt Mode 1.4
Video resolution	4K/30Hz
Network	WiFi module: RTL8821CS
WiFi protocol	IEEE 802.11a/b/g/n/ac Wi-Fi compliant
Frequency range	2.4~2.4835GHz (2.4 GHz ISM Band) / 5.15~5.85GHz (5.0 GHz ISM Band)
Number of antennas	1 x built-in
Function Key	Single click: Stop/Restart video display Long press 5s: Enter pairing mode Long press 10s: Factory reset
Cable length	15cm
LED working status	System startup: light on; Not paired or pairing: quick flashing; Connecting: slow flashing; Monitoring: light on; Disconnecting: light off; Factory Reset: quick flashing.
Max. power consumption	3W for monitoring; 8W for full loading
Receiver	
Dimensions	90mm x 90mm x 19.5mm LxWxH
HDMI Video resolution	4K/30Hz
WiFi protocol	IEEE 802.11a/b/g/n/ac Wi-Fi compliant
Frequency range	2.4~2.4835GHz (2.4 GHz ISM Band) / 5.15~5.85GHz (5.0 GHz ISM Band)
Number of antennas	1 x built-in
VGA	Resolution/Refresh rate 1080p/60Hz/24/bit; 720p/60Hz/24bit;480p/60Hz/24bit
Power supply	5V/2A/10W via USB-C™PD port (USB charger not included)
Cable	USB-A to USB-C™ cable (80cm)
LED Working status	White light
Display protocol	Private protocol
Function Key	Long press 5s to enter re-pair mode

